

**NKOSITHANDILEB SOLAR**

# **Solar glass light transmittance**



## Overview

---

What is visible light transmittance?

Visible Light Transmittance ( $T_v$ , %) is the percentage of incident light in the wavelength range of 380 nm to 780 nm that is transmitted by the glass.

Visible Light Outdoors/Indoors ( $R_{e\ out/in}$ , %) is the percentage of incident solar energy directly reflected by the glass.

What is visible light transmittance (VLT)?

Visible light transmittance (VLT) is a percentage of the visible portion of the solar energy spectrum coming through the glass. It is expressed as a figure between 0 (no light) and 100 (all light). This value measures the ability of the glass to transmit light and facilitate daylighting.

What is the difference between visible transmittance and visible reflectance?

Visible transmittance ( $\tau_v$ ) and visible reflectance ( $\rho_v$ ) refer to the ratio of the beam of visible light vertically incident on a glass surface to the incident beam of transmitted light or reflected light.

What is solar energy direct transmittance ( $T_e$ )?

Solar Energy Direct Transmittance ( $T_e$ , %) is the percentage of incident solar energy in the wavelength range of 300 nm to 2500 nm that is directly transmitted by the glass. Solar Direct Reflectance Outdoors/Indoors ( $R_{e\ out/in}$ , %) is the percentage of incident solar energy directly reflected by the glass.

## Solar glass light transmittance

---

Visible Light Transmittance ( $T_v$ , %) is the percentage of incident light in the wavelength range of 380 nm to 780 nm that is transmitted by the glass. Visible Light Outdoors/Indoors ( $R_{e\ out/in}$ , %) is the percentage of incident solar energy directly reflected by the glass.

Visible light transmittance (VLT) is a percentage of the visible portion of the solar energy spectrum coming through the glass. It is expressed as a figure between 0 (no light) and 100 (all light). This value measures the ability of the glass to transmit light and facilitate daylighting.

Visible transmittance ( $\tau_v$ ) and visible reflectance ( $\rho_v$ ) refer to the ratio of the beam of visible light vertically incident on a glass surface to the incident beam of transmitted light or reflected light.

Solar Energy Direct Transmittance ( $T_e$ , %) is the percentage of incident solar energy in the wavelength range of 300 nm to 2500 nm that is directly transmitted by the glass. Solar Direct Reflectance Outdoors/Indoors ( $R_{e\ out/in}$ , %) is the percentage of incident solar energy directly reflected by the glass.

Conventional glazing consisting of a single or multiple glass pane (s) exhibits high visible light transmittance and solar heat gain coefficient, which can be a double-edged sword, i

Explanation of terms according to JIS R 3106: 1998 JIS R 3107: 1998. Visible Light Transmittance ( $T_v$ , %) is the percentage of incident light in the ...

Visible Light Transmittance (VLT) Visible light transmittance (VLT) is a percentage of the

visible portion of the solar energy spectrum ...

Transmittance is the key factor to the quality of solar glass. At present visible light transmittance (380-780 nm) and solar direct transmittance (300-2500 nm) were used to evaluate the light ...

Visible Light Transmittance (VLT) Visible light transmittance (VLT) is a percentage of the visible portion of the solar energy spectrum coming through the glass. It is expressed as ...

Solar glass is a specialized low-iron, tempered soda-lime silicate glass, often enhanced with an anti-reflective coating. This combination delivers ultra-high light transmittance, superior ...

Explanation of terms according to JIS R 3106: 1998 JIS R 3107: 1998. Visible Light Transmittance ( $T_v$ , %) is the percentage of incident light in the wavelength range of 380 nm to 780 nm that is ...

Glass in building -- Determination of light transmittance, solar direct transmittance, total solar energy transmittance, ultraviolet transmittance and related glazing ...

In this paper we analyse the spectral transmission of solar radiation of widely used materials using the transmittance parameter. The measurements were performed on clear ...

Transmittance is the key factor to the quality of solar glass. At present visible light transmittance (380-780 nm) and solar direct transmittance (300-2500 ...

Based on these transmittance spectra, solar transmittance measurement software was used to calculate solar transmittance and ...

Based on these transmittance spectra, solar transmittance measurement software was used to calculate solar transmittance and visible light transmittance values. The results

...

Visible Transmittance and Visible Reflectance Visible transmittance ( $\tau_v$ ) and visible reflectance ( $\rho_v$ ) refer to the ratio of the beam of visible light vertically incident on a glass

...

Conventional glazing consisting of a single or multiple glass pane (s) exhibits high visible light transmittance and solar heat gain coefficient, which can ...

## Contact Us

---

For catalog requests, pricing, or partnerships, please contact:

### **NKOSITHANDILEB SOLAR**

Phone: +27-11-934-5771

Email: [info@nkosithandileb.co.za](mailto:info@nkosithandileb.co.za)

Website: <https://www.nkosithandileb.co.za>

*Scan QR code to visit our website:*

